

TWO-POST - I12

NEW!

Engineered to perform... Built to last!

Powder coat finish;
more durable than
conventional finishes

Padded shut-off bar to
prevent damage caused by
lifting a vehicle too high

Two heavy-duty
push-type cylinders
designed to minimize
down-time by
requiring little
maintenance



Shown: Model I12
12,000 lbs. capacity

Engineering Excellence

Forward's U.S. engineers have over 29 years of combined experience designing automotive lifts for service and repair shops. Forward's philosophy is to own our designs rather than use someone else's off the shelf product.

Product Integrity

21st century design tools allow us to create, control and validate our designs to ensure maximum performance. Forward lifts are rigorously tested to meet quality and durability standards. All product families are proof load tested to 1½ times rated capacity and rigorously cycle tested.



**Two-Post
I12 is
Gold
Certified**

**FORWARD
LIFT**

I12 Series Features:

- 12,000 lbs. capacity for raising most passenger cars, trucks and vans.
- The I12 is third party certified by ALI.
- Hydraulic cylinders in each column
 - Full stroke
 - Cylinder rod concealed inside carriage
- Overhead cable equalization.
- Single point lock release
- Large rubber-padded swivel adapters with extra height extensions (4-1/2" and 8-1/2") are standard.
- Spring operated arm restraints, disengage at floor level.
- Padded overhead height limit switch bar.
- Durable powder coat finish - standard color of lift is blue with yellow arms. Red lift with yellow arms also available at no extra cost.



Shown: Model I12
12,000 lbs. capacity

Available Options:

- Adapter storage bracket kit
- Special truck adapters
- Air/Electric work station with air regulator and oiler



Shown: Model I12
12,000 lbs. capacity

Specifications	I12
Capacity	12,000 lbs. (5443kg)
Rise Height	82-1/2" (2095mm) with adapters
Adjustable Overall Height	165-1/4" (4197mm), 177" High Setup (4496mm)
Overall Width	150-3/8" (3822mm)
Drive Through	109-1/2" (2781mm)
Floor to Overhead Switch	159-3/8" Low (4051mm), 169-1/2" High (4305)
Front Arm Reach	Min. 38-1/2" (978mm), Max. 57-1/2" (1461mm)
Rear Arm Reach	Min. 38-1/2" (978mm), Max. 57-1/2" (1461mm)
Lifting Pad Height	6" (152mm)
Lifting Pad Height w/Short Ext.	10-1/2" (267mm)
Lifting Pad Height w/High Ext.	14-1/2" (368mm)
Width Between Columns	123-1/4" (3131mm)
Motor	2 HP
Voltage	208v - 230v
Speed of Rise	60 seconds

Specifications subject to change without notice or liability



Forward Lift
996 Industrial Drive
Madison, IN 47250

Phone: 800.423.1722
Fax: 812.273.7329
www.forwardlift.com

Li# Forward I12_2009.10

©2009 Forward Lift, Forward Lift is a brand of R.L. Consolidated, A Dover Company. All rights reserved. Unless otherwise indicated, Forward Lift, R.L. Consolidated, Dover and all other trademarks are property of Dover Corporation and its affiliates.